



D160 Loader

- Compatible with the 3032E and 3038E
- Rigid mounted with parking kit available
- Easy maintenance for increased uptime
- 977 pounds (444 kg) of lift capacity

Build Your Own

[Find a Dealer >](#)

[View Compact Utility Tractor Implements Brochure >](#)

Features

[Expand All](#)

+ End-of-pin lubrication - Easy maintenance

+ Parking stand kit

Specifications

Key Specs

Maximum lift height (A)

2140 mm
84 in.

Lift capacity at full height

Measured at pivot (U)
1186 lb
539 kg
Measured at 500 mm ahead of pivot (V)
845 lb
384 kg

Boom breakout force

Measured at pivot (Y)
1704 lbf
760 kgf
Measured at 500 mm ahead of pivot (Z)
1204 lbf
537 kgf

Bucket rollback force capacity

At ground-level line (ZZ)
1422 lbf
634 kgf

Clearance at full height - bucket dumped (C)

1596 mm
63 in.

Dump angle, degrees (E)

43.8 degree (angle)

Rollback angle, degrees (G)

31.4 degree (angle)

Tractor

Model

3032E, 3038E

Front tire

25x8.50-14 4PR R4

Rear tire

15.00-19.5 4PR

Wheelbase

60 in.

1525 mm

Pump capacity

5.3 gpm

Rated pressure

2495 psi

[Show More](#)

Shop and Buy

[Build Your Own](#)[Buy Online](#)[Buy Parts](#)[Find a Dealer](#)[John Deere Financial](#)

Maintenance and Support

[Service Info](#)[Product Safety](#)

You May Also Be Interested In

[John Deere Rewards](#)[Used Equipment](#)[View California Products](#)

Product features are based on published information at the time of publication. Product features are subject to change without notice. Contact your local John Deere dealer for more information.