

FDR16 Series Flat Deck Grooming Mowers

List	Specifications & Capacities		
Model Numbers	FDR1648	FDR1660	FDR1672
Maximum Horsepower - Engine	40 horsepower		
Cutting Width	48"	60"	72"
Overall Width	50 1/2"	62 1/2"	74 1/2"
Height	36"	36"	36"
Length	60"	67"	72"
Weight	486#	577#	619#
Cutting Height (1/2" increments)	3/4" - 5 1/4"		
Deck Material Thickness	3/16"		
Blade Tip Speed	16,203 FPM	18,195 FPM	18,130 FPM
Blade Construction -3 ea.	1/4" x 2 1/2" x 16 7/8" Heat Treated Alloy Steel	1/4" x 2 1/2" x 21" Heat Treated Alloy Steel	1/4" x 2 1/2" x 25" Heat Treated Alloy Steel
Blade Options	Standard Blades: Medium Lift Optional Blades: Low Lift, High Lift & Mulching		
Blade Overlap	1 1/4"		
Blade Spindles	1 3/8" dia., Cast Iron Greasable Hubs		
Discharge	Rear		
Hitch	Category I		
Lower Hitch	Floating Clevis with Plated Pins		
Top Link	Floating Clevis		
Castered Gauge Wheels	3 1/4" x 10" Solid Rubber		
Caster Wheel Spindle	1" Diameter with Nylon Bushing		
Drive Train	540 rpm power take-off Cast Iron Housing Gearbox With Beveled Gears, 1:2.83 Ratio Spring Loaded Single V-Belt		
Gearbox Oil Capacity & Type	2.5 Pints of 80-90W EP Gear Lube		
Driveline	Heavy-Duty w/quick coupler, ASAE Cat 2		
Front Roller	Optional		
Quick Hitch Compatible	No	Yes	Yes

